



RECYCLED LABEL

Technical data sheet

FACE MATERIAL:

- Description** An environmental friendly paper, made from 100% Post Consumer Waste. The paper is bleached without chlorine.
- Use** The product is ideal for label applications using variable information printing such as address, instruction and inventory labels for the small office and home office market..

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	80	105

ADHESIVE:

- Description** A general purpose permanent, acrylic based adhesive.
- Performances** It's characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates.
- Shelf life** 2 years stored at 22°C and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	17	0	-20	+80

BACKING PAPER:

- Description** Kraft layflat release liner with high environmental credentials. The paper is produced from recycled paper up to recycled content of 100%
- Application** For laminates where thin backing is needed for information labelling.

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	203	80

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.