



DOUBLESIDE ADHESIVE

Technical data sheet

LINER:

Description One side siliconised yellow glassine

TECHNICAL DATA	Weight	Caliper	Transparency
	g/m2	Microns	%
	60	54	50

ADHESIVE:

Description Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP)

Shelf life 2 years under the following storage conditions: 20-22 °C and 50 % RH

TECHNICAL DATA	Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	11	5	-40	+100

LINER:

Description One side siliconised yellow glassine

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	61	54

ADHESIVE:

Description Acrylic permanent adhesive. Good adhesion on a wide variety of materials including apolar substrates (like PE and PP)

TECHNICAL DATA	Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	11	5	-40	+100

LINER:

Description One side siliconised yellow glassine

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	61	54

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.

