



POLYPROPYLENE WHITE

Technical data sheet

FACE MATERIAL:

- Description** A white bi-axially oriented, polypropylene film with a print-receptive topcoat.
- Use** The modified acrylic top coating can be printed by conventional printing techniques including flexo, screen, offset, letterpress. The topcoat is designed for optimum ink adhesion. The face material is suitable for Thermal Transfer printing. The material has excellent register properties especially when a high number of colour are used

TECHNICAL DATA	Weight	Caliper
	g/m ²	Microns
	59	57

ADHESIVE:

- Description** A general purpose permanent, acrylic based adhesive.
- Performances** It's a clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance, even on apolar substrates.
- Shelf life** 2 years under storage conditions : 20-25° C ; 40-50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	11 N/25mm	5	-20	+80

BACKING PAPER:

- Description** A white, supercalendered glassine paper.
- Application** Applications are predominantly in market segment where rigid containers are used (E.g. Glass, PET). Due to fairly rigid nature of the film care should be taken with use on non-uniform surfaces and where a very high level of squeezability is desired.

TECHNICAL DATA	Weight	Caliper
	g/m ²	Microns
	61	54

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.