



TRANSPARENT GLOSSY POLYESTER

Technical data sheet

FACE MATERIAL:

- Description** Transparent, gloss coated heat stabilized polyester film
- Use** Specially designed for logistics, products, industrial applications including variable information.

| TECHNICAL DATA | Weight | Caliper |
|----------------|--------|---------|
| | g/m2 | Microns |
| | 71 | 50 |

ADHESIVE:

- Description** A clear, acrylic , water bone permanent adhesive
- Performances** Good water resistance once labelled. Good adhesion properties and heat resistance. Limited adhesion at low temperature.
- Shelf life** 2 years stored at 22°C and 50% RH

| TECHNICAL DATA | Initial Tack | Application Temperature (min) | Service Temperature (min) | Service Temperature (max) |
|----------------|--------------|-------------------------------|---------------------------|---------------------------|
| | N/mm | °C | °C | °C |
| | 9 | +5 | -20 | +100 |

BACKING PAPER:

- Description** White woodfree kraft backing paper

| TECHNICAL DATA | Weight | Caliper |
|----------------|--------|---------|
| | g/m2 | Microns |
| | 100 | 97 |

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.