

ANSER™

2016/02/02 1



Print Preview

16.02.01
16.02.15


Real-time Printing Report

Product Counter : 0

U2
smart

Model: U2 Smart Printer
Imp. No. : AZI 555A 830
Manufactured in Taiwan
by ANSER CODING INC.
PIN: T10A052510 CE FC

S/N: 30E850
30E850





The U2-Smart offers the most cost-effective solution with exclusive ink portfolio for Porous & Semi-porous printing applications.



Compact Size with 3.5-inch LCD Screen

Feature a larger screen to provide a better user experience, while maintaining its compact body size for hassle-free installation and easy integration.



Pocket-sized Remote Keypad

Handy and compact remote keypad with comprehensible design for easy operation.



Dust Cover Design

Help to protect cartridge from getting damaged in dusty environment.



Anti-Shock Mechanism Design

Anti-Shock Mechanism design to eliminate the unexpected damage to your printer with ANSER's unique protective design.



High Readable Rate Barcodes

Capable of printing crisp 1D & 2D barcodes including EAN 128, Code 128, Code 39, Data Matrix, QR Code, and etc.



Zero-Maintenance

The ink cartridge design eliminates unnecessary printhead services; it is truly zero-maintenance and has drastically decreased your total cost of ownership.



Friendly UI & Intelligent Dashboard

Simple yet elegant user interface for easy operation. The intelligent dashboard design monitors the printer status and provides real-time system notifications.



USB 2.0 Compatible

Multiple functions including software update, data backup and stand-alone USB keyboard operation.



Automatic Ink Identification


Automatically identifies and selects the proper firing parameter to ensure the best print quality.

U2TM
smart



**BUY 1 GET 1
FREE**

Available at selected countries.



ANSER CODING INC

16.02.01
16.02.15

30mm X 30mm
30mm X 30mm
30mm X 30mm
PLANED TIMBER
PLANED TIMBER
PLANED TIMBER

08.06.2011
12:23



U2-Smart Specifications:

Display	3.5" Color LCD with LED backlight
User Interface	Simple and easy-to-use operating system
Input Device	Pocket-sized IR remote keypad
Available Languages	English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Chinese (Traditional & Simplified)
LED Indicators	Alarm, Ink low, Print, Run, Remote on/off
Print Engine	Hewlett-Packard Thermal Ink Jet Technology
Print Resolution & Print Speed	600 x 300 dpi (76.2 m/min) Print quality is dependent on resolution and speed
Print Distance	Recommended 6mm
Print Height	Up to 4 lines and 12.7mm (0.5"). Selectable font size from 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm
Print Capability	Alphanumeric, logos, date/time, shift code, counter, lot box code
Barcodes	Code-128, ITF-14(SCC-14), NVE(SSCC-18), EAN-128, PDF417, Data Matrix, QR Code, DUN-14, GS1 DataBar, UPCA, UPCE, EAN-13, EAN-8, Code 25 Interleaved, Codabar, Code-39
Electrical Requirements	AC 100V~240V, 50/60Hz
Weight	0.49kg (1.08 lbs) - Cartridge and brackets not included
Dimensions	114 (L) x 76 (W) x 60 (H) mm
Mounting Orientation	Horizontal or downside
Message Storage Capacity	Store up to 999 messages
Operating Temperature	5°C – 40°C (41°F – 104°F)
Data Interface	RS485 & USB

Optional Accessories:

Encoder	Provide high print quality on unstable conveyor
Photocell	Provide more reliable and precise sensing parameter
Alarm Kit	Alert users in the event of an incident



WWW.ANSER-U2.COM



ANSER CODING INC. | info@anser-u2.com