



ANSER



U2 SmartONE



U2-SmartONE™ Features



High Readable Rate Barcodes

Capable of printing crispy 1D & 2D barcodes including EAN 128, Code 128, Code 39, Datamatrix, QR and etc.



Zero-Maintenance

The ink cartridge design eliminates unnecessary printhead services; it is truly zero-maintenance and has drastically decreased your total cost of ownership.



Pocket-sized Remote Keypad

Handy and compact remote keypad with comprehensible design for easy operation.



Friendly UI & Intelligent Dashboard

Simple yet elegant user interface for easy operation. The intelligent dashboard design monitors the printer status and provides real-time system notifications.



Automatic Ink Identification

Automatically identifies and selects the proper firing parameter to ensure the best print quality.



Anti-Shock Mechanism Design

Anti-Shock Mechanism Design Eliminate the unexpected damage to your printer with ANSER's unique protective design.

U2-SmartONE™ Specifications

Display	3.5" Color LCD with LED backlight
User-interface	Simple and easy-to-use operating system
Input Device	Pocket-sized IR remote keypad
Available Languages	English, Japanese, French, German, Spanish, Portuguese, Russian, Korean, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian, Bulgarian, Chinese (Traditional & Simplified), Polish, Farsi, Arabic
LED Indicators	Alarm, Ink Low, Print, Run, Remote on/off
Print Engine	Thermal Ink Jet Technology
Print Resolution & Print Speed	300 dpi (60m/min) Print quality is resolution & speed dependent
Print Distance	Max 6mm
Print Height	Up to 25.4mm(1-inch). Selectable font size: 5.4mm, 7.2mm, 11mm, 16mm, 20mm, 25.4mm
Print Capability	Alphanumeric, logos, date/time, shift code, counter, lot box code
Barcodes	EAN8, EAN13, EAN14, EAN128, UPCA, UPCE, CODE39, CODE128, TF14 (SCC-14), NVE18 (SSCC-18), C25INTER, CODABAR, PDF417, DATAMATRIX, QR CODE
Power Adapter	Input AC 100V~240V, 50/60Hz Output DC 12V/5A, 60W
Weight	0.49kg (1.08 lb.) - excluding cartridge and bracket
Dimensions (L/W/H)	114x76x60 (mm)
Mounting Orientation	Horizontal or downside
Message Storage Capacity	Store up to 999 messages
Operating Temperature	5°C - 40°C (41°F - 104°F)
Data Interface	RS485 & USB Host

Optional Accessories

Encoder	Provide high print quality on unstable conveyor
Photocell	Provide more reliable and precise sensing parameter
Alarm Kit	Alert users in the event of an incident




WWW.ANSER-U2.COM

30
YEARS OF INNOVATION
SINCE 1986

ANSER CODING INC. | info@planet-group.it

U2 SmartONE™
you too, SmartONE



THE ONE & ONLY

Introducing U2-SmartONE™
the world's first ONE inch TIJ printer
ONLY at ANSER



1. Solid 1-inch cartridge, specially designed for industrial coding market
2. No stitching required, with seamless print quality for higher readable rate
3. Compact-sized for easy installation and system integration

